

WSC 204 CONTROL UNIT

CONTROLS SMOKE CONTROL



■ Applications



■ WSC 204 CONTROL UNIT

- Single zone 4.8amp 24VDC smoke control panel.
- Complete with inputs for natural ventilation (switch, rain sensor etc).
- When installed correctly unit is compliant with EN12101-10.
- Complete with 72 hour battery back up on mains failure.
- Complete with lead acid batteries.
- Open circuit cable detects power supply failures, removal of batteries etc.
- Facility to link several panels to for larger buildings.
- Steel enclosure also available.

COMPATIBLE ACTUATORS:

WMU 86/88



WMU 836



WMX 804



WMX 826



Other actuators compatible, please contact a member of staff for further information.

TECHNICAL DATA:

CODE	WSC 204
VOLTAGE (INPUT)	230VAC
VOLTAGE (OUTPUT)	24VDC
OUTPUT CURRENT	4.8A
IP RATING	IP20
COLOURS	WHITE
DIMENSIONS	368 x 353 x 97mm
INPUTS	SSR, FIRE ALARM, WSK 320, WSK 100

INPUTS:

SSR

Smoke Sensor



Fire Alarm



WSK 320

Break Glass Call Point



WSK 100

Manual Switch



Additional inputs available, please contact a member of staff to find out more.

