

# SV-W-GL

## GLAZED LOUVRE

### SIZES

Bespoke

### FREE AREA

1 m<sup>2</sup> or 1.5 m<sup>2</sup>



### DESCRIPTION

The SV-W-GL Louvre Window is preferred by many of our clients due to its outstanding advantages in regard to ventilation, weather tightness and thermal protection, as well as a high degree of security (burglar proof RC2). The glass louvres are framed with aluminium profiles.

The SV-W-GL is certified for use as NSHV (Natural Smoke and Heat Ventilation) device according to EN 12101-2, furthermore it is available ball protection proof suitable for use in sports facilities (DIN 18032-3)

### APPLICATION



COMFORT  
VENTILATION



SMOKE  
VENTILATION

### CERTIFICATION

Certified and tested in accordance to EN 12101-2



## TECHNICAL DATA

Frame	AL-profiles, thermal broken
Blades	Insulated glass, aluminium profile
Geometric Free Area	1 m <sup>2</sup> or 1.5 m <sup>2</sup> (depending on vent size)
Voltage	24V DC
Opening Speed	> 60 secs
Current Consumption	0.7 A
Colour	Custom RAL colour
Certification	EN 12101-2
Delivery Includes	1 x Vent & 1 x Actuator
Cable Dimensions	3-Core

## CONTROLS



**WSC 204**  
AOV Control Unit



**WSK 320**  
Override Switch



**SSR-D**  
Smoke Sensor



**S60**  
Rocker Switch

## DIMENSIONS

