

# PSU-2/4/8

## TRANSFORMER

### VOLTAGE

Input = 230V AC, Output = 24V DC

### MOTOR LINES

1

### MOTOR LOAD

2.0 A (PSU-2), 4.0 A (PSU-4) or  
8.0 A (PSU-8)



### DESCRIPTION

Control for integration of 24V DC actuators in 230 V~ systems. Output current 2 A (PSU-2), 4 A (PSU-4) or 8 A (PSU-8). Connected actuators can be controlled by ventilation buttons wired on 230 V~. Allows to integrate 24 V- actuators of greater lifting power in 230 V~ ventilation systems, or to add 24 V- actuators to existing 230 V~ ventilation systems. Optionally available with contacts for forwarding the actuator positions Open / Closed (option PK-SA). For using this option, actuators with additional limit switches are required.

### INPUTS FOR

Switch  
Key Switch

### APPLICATION



COMFORT  
VENTILATION

## TECHNICAL DATA

Primary Voltage (Input)	230V AC
Secondary Voltage (Output)	24V DC
Motor Load	2.0 A (PSU-2) 4.0 A (PSU-4) or 8.0 A (PSU-8)
Motor Lines	1
Inputs	230V AC Control Unit or Switch
Operating Condition	-5°C - +75°C
Battery Backup	No
Size	200 x 120 x 90 mm (PSU-2) 255 x 180 x 75 mm (PSU-4/8)
Protection Type	IP 66
Delivery	1 x Control Unit

## PART CODES

PSU-2	-	PSU-2 Transformer 24 V 2 A
PSU-4	-	PSU-4 Transformer 24 V 4 A
PSU-8	-	PSU-8 Transformer 24 V 8 A

## COMPATIBLE WITH



**MICRO EVO**  
Chain Actuator



**MICRO L**  
Chain Actuator



**MICRO XL**  
Chain Actuator



**S08**  
Spindle Actuator

(Multiple 24V DC actuators, total load must not exceed 2.0 A (PSU-2), 4.0 A (PSU-4) or 8.0 A (PSU-8) max.)